

P.O.Box 11234 Jubail Ind'l City 31961 -KSA  
Tel.: 966 3 341 1179, Fax: 966 3 341 1344

## **TECHNICAL SPECIFICATION**

**Product Name: LIGHT BASE OIL AROMATIC OIL**

| #  | PARAMETERS                   | ASTM D | UNIT     | SPECS.        |
|----|------------------------------|--------|----------|---------------|
| 1  | Appearance                   | Visual | -        | Black         |
| 2  | Density @ 15°C               | 7042   | g/mL     | 0.890 – 0.970 |
| 3  | Kinematic Viscosity @ 40 °C  | 445    | cSt      | 35 - 80       |
| 4  | Kinematic Viscosity @ 100 °C | 445    | cSt      | 5.0 – 9.6     |
| 5  | Flash Point, COC, Min.       | 92     | °C       | 190           |
| 6  | Flash Point, PMCC, Min.      | 93     | °C       | 170           |
| 7  | Neutralization No. , Max.    | 974    | mg KOH/g | 0.1           |
| 8  | Ash Content, Max.            | 482    | Wt.%,    | 0.8           |
| 9  | Sulphur Content, Max.        | 4294   | Wt.%,    | 1.9           |
| 10 | Aromatics , Min.             | 2007   | Wt.%,    | 45            |

### **Applications:**

This Product useful in the Rubber Process Industries for making rubber-based equipment like conveyor belts, automotive components, tyre and floor mats, etc.

**Issue Date:** 5<sup>th</sup> November, 2024

**Doc #:** FM:TS:57

**Revision:** 5

**Page #:** 1 of 1