

P.O.Box 11234 Jubail Ind'l City 31961 -KSA  
Tel.: 966 3 341 1179, Fax: 966 3 341 1344

## **TECHNICAL SPECIFICATION**

Product Name: **UNILUBE FUEL OIL**

Product Code: **UFO**

#	PARAMETERS	ASTM D	UNIT	SPECS.
1	<b>Density @ 15°C</b>	7042	Kg/m3	<b>820 - 870</b>
2	<b>Kinematic Viscosity @ 40°C</b>	445/7042	cSt	<b>1.50 – 6.0</b>
3	<b>Sulphur Content, Max.</b>	4294	mass %	<b>0.5</b>
4	<b>Water Content, Max.</b>	95	Wt %	<b>0.05</b>
5	<b>Flash Point (PMCC)</b>	93	°C	<b>60-65</b>
6	<b>Strong Acid Number, Max.</b>	974	mg KOH/gm	<b>0.05</b>
7	<b>Total Acid Number, Max.</b>	664/974	mg KOH/gm	<b>0.5</b>

### **Applications:**

1. It is used in cutter stock oils such as fuels to reduce the viscosity of fuel
2. It is also used in carbureted water gas and oil-gas plants
3. Moreover it also used in small furnaces, including domestic and Industrial heating

<b>Issue Date:</b> 5 <sup>th</sup> November , 2024	<b>Doc #:</b> FM:TS: 40
<b>Revision:</b> 5	<b>Page #:</b> 1 of 1